
TWIN TECHNOLOGY LIMITED COMPANY

**2022** 





# CONTENT

TWIN Technology Limited Company - About Us	01
TWIN IQ-Smart Home Building Automation Systems	
Ligting	
Blinds/Shutter	
Air Conditioning	
Security	05
General Informations	
Contracts	07
1. ISTANBUL ARCHAELOGICAL MUSEUM / TURKEY	08-11
2. REPUCLIC OF PRESIDENTIAL RESIDENCE HUBER / TURKEY	12
3. GRAND MOSQUE ÇAMLICA / TURKEY	13-14
4. REPUCLIC OF PRESIDENTIAL RESIDENCE AHLAT / TURKEY	
<ul><li>5. NOW BUSINESS CENTER / TURKEY</li><li>6. ÇAMLICA- MUSEUM OF ISLAM CIVILIZATIONS / TURKEY</li></ul>	16-18
7. ISFANBUL SHOPPING CENTER / TURKEY	19-24
8. ZONGULDAK UZUN MEHMET MOSQUE / TURKEY	38-39
9. ATASUN OPTIC / TURKEY	40
10. MERMERCILER OSB MOSQUE / TURKEY	41-42
11. MİMAR SİNAN OSB MOSQUE / TURKEY	43-44
12. KAYSERİ OSB FEVZİ MERCAN MOSQUE / TURKEY	45-47
13. TURK FATIH TUTAK RESTAURANT / TURKEY	48-49
Products	50-72
Special Fabrication	73-91
Samples	92-107
Referances	108

### **TWIN TECHNOLOGY LIMITED COMPANY**



Our company, which has 20 years of experience in the electronics sector, operates in the field of LED Lighting with the TWIN brand.We serve as a brand as a result of the integration of **technology** and **experience** from the past to the present.



We set out with the aim of long-lasting, comprehensive and comprehensive use, which is to produce LED lights. We are growing even more the next day in this way to transform light into an **efficient** and **economical** lighting tool.

We continue to work non-stop with our expert team in order to provide the most **effective** and **quality** products to LED technology that changes day by day. Sending lighting and lighting automation solutions that make a difference and add value to your projects with our expert teams in many **different project types**, from large areas to residential projects with LED lighting systems. With our expert team in the field of your **internal and external lighting products**, systems and automation, such as offices, shopping malls, hospitals, markets, stores, work areas, living projects and commercial areas, we are working non-stop to make them project conceptual and energy efficient.



Act with the knowledge that effective messages will be given with the right lighting, but a correct project design is required in this regard. We work by considering this idea in all projects we think of. With this feature, we are among the companies that are preferred by the customer, who have a real **art perspective**.



Our company has adopted **customer satisfaction** as its main target.



Our company, which has 20 years of experience in the electronics sector, operates in the field of LED Lighting with the TWIN brand.

### **TWIN IQ** Smart Home Building Automation Systems

We plan to use the latest technology products of today in your villa project and will follow an engineering understanding to offer spaces that improve the quality of your life. We developed a project in which the system has selfcontrol tools, central monitoring and control are possible, and user errors are minimized. Thanks to the EIB/KNX system, serious energy savings and comfort will be achieved, and advantages with high returns will be gained. It is worth indicating that the controls you can request in the future can easily be integrated into the system.



• You can perform checks on the systems required for a comfortable life such as

optimum temperature, air, lighting, electric blinds in accordance with personal life in each room, within scenarios, automatically or manually according to the ambient conditions; you can monitor the entire system with central controls and save energy.  $\neq 0$ 

• Thanks to the internationally accepted KNX communication standard,

instead of being dependent on the products of a single manufacturer, all the devices using this protocol can be integrated into the system. In this way, it is possible for all desired functions to take effect immediately or later in the system.



• KNX is an open data bus standard and an integrated communication protocol used for all these applications. Thanks to the standardization it brings, it provides additional comfort, security, and energy-saving functions to be integrated immediately or later; thus, it is an ideal platform for the automation system to be flexibly extended.

### **LIGHTING** 80%

#### LIGHTING

- All lighting can be turned on and off via a button or a touch panel from any suitable place in the house with On-Off control,

- Using dimmer lighting control, the most ideal lighting level can be set for a dinner with the candle light ambience, a well-lit working environment, or for reading,

- Creating scenarios and creating the desired ambiance with a single touch (lighting scenarios such as dinner, chatting, reading), - With the presence detectors, ensuring lighting control and energy saving through a relatively sensitive detection compared to a motion detector,

- Thanks to the light sensor, turning on the desired lighting when the sun goes down, and to turn them off when the sun is up,

- The feature of monitoring and controlling the on or off status of the lighting systems of all areas through the touch screen, - Room or floor-based lighting control,

- The feature of controlling all the power sockets,

- The feature of automated adjustment of the brightness to a level that will not disturb your eyes thanks to the Brightness Sensor,

- With its Timer and Logic features, it provides timing and logic controls to prevent user errors, thereby saving energy...



#### **BLINDS/SHUTTER**

- With the Blinds/Shutter Control, you can open and close all the blinds from anywhere in the house via the button or touch panel,

- With the Brightness Sensor, the light sensor automatically adjusts the position of the blinds-shutters according to the detected light level. The shading in your building is automatically provided during hot summer days. Or, in winter, when the sun goes down early, heat-insulated shutters can automatically adjust their own positions, - Thanks to the Weather Station, the desired lighting can be turned on when it gets dark or turned off when the sun is up,

- It is possible to create scenarios and the desired ambiance with a single touch (such as dinner, chat, reading Blinds/Shutter scenarios).

#### AIR CONDITIONING

- Thanks to the air conditioning control, the temperatures of different spaces are kept at the most reasonable level. The desired temperature value can be set via the smart switches and from the center according to the changing conditions, and usage limitations for rooms can be imposed.

- When doing these controls, you can use all the functions such as lighting, air conditioning, and scenarios together via the smart switch with thermostat, which is compatible with the architectural concept of the room... - You can control Air Conditioning and Fan Coil systems in the rooms or the entire house,

- The feature of using on/off control in heating systems, and room-based controls,

- The feature of switching on and off remotely when you are not at home,

- Suitable and separate temperature levels for night and day time or for desired times - Standby temperature level when the room is empty.

- Central monitoring and control.

- You can get status information of all the systems in your house via mobile devices such as Iphone,

- Ipad, android and you can accordingly make lighting, heating/cooling, blinds controls for each room when you are inside or outside the house.



#### SECURITY

- Motion detector protection in different areas,

- Protection via fire, gas, and smoke detectors,

- Interfering with water leakages with leakage sensors

### **General Information**

Primary contacts for sales/client services	Name: Mr. Umit BARATALI Email: umit@twinltd.com.tr
Address	Cumhuriyet Mahallesi Silahşör Caddesi No: 2/20 Now Plaza Bomonti Şişli / İSTANBUL/TURKEY
Telephone:	+90505 257 70 65
Type of Organization	Limited Company
Type of Business	Lighting Fixture production, sales and application
Year Established Year Incorporated	2013 2013
Summary of main business activities	<ul> <li>Project Consultancy</li> <li>Lighting Design</li> <li>Production &amp; Assembly</li> </ul>
No. of Employees	25
In-house working language(s)	Turkish



### Contracts

- 1. ISTANBUL ARCHAELOGICAL MUSEUM / TURKEY
- 2. REPUCLIC OF PRESIDENTIAL RESIDENCE HUBER / TURKEY
- 3. GRAND MOSQUE ÇAMLICA / TURKEY
- 4. REPUCLIC OF PRESIDENTIAL RESIDENCE AHLAT / TURKEY
- 5. NOW BUSINESS CENTER / TURKEY
- 6. ÇAMLICA- MUSEUM OF ISLAM CIVILIZATIONS / TURKEY
- 7. ISFANBUL SHOPPING CENTER / TURKEY
- 8. ZONGULDAK UZUN MEHMET MOSQUE / TURKEY
- 9. ATASUN OPTIC / TURKEY
- 10. MERMERCILER OSB MOSQUE / TURKEY
- 11. MİMAR SİNAN OSB MOSQUE / TURKEY
- 12. KAYSERİ OSB FEVZİ MERCAN MOSQUE / TURKEY
- 13. TURK FATIH TUTAK RESTAURANT / TURKEY



### 1. ISTANBUL ARCHAELOGICAL MUSEUM / TURKEY









### 1. ISTANBUL ARCHAELOGICAL MUSEUM / TURKEY













### 2. REPUCLIC OF PRESIDENTIAL RESIDENCE HUBER / TURKEY










#### 3. GRAND MOSQUE ÇAMLICA / TURKEY















#### 4. REPUCLIC OF PRESIDENTIAL RESIDENCE AHLAT / TURKEY





#### 5. NOW BUSINESS CENTER ISTANBUL / TURKEY












#### 5. NOW BUSINESS CENTER ISTANBUL / TURKEY

























































































### 7. ISFANBUL SHOPPING CENTER / TURKEY







### 8. ZONGULDAK UZUN MEHMET MOSQUE / TURKEY
















### 9. ATASUN OPTIC / TURKEY

### COMPANY PROFILE 2022






### 10. MERMERCİLER OSB MOSQUE / TURKEY








### 11. MİMAR SİNAN OSB MOSQUE KAYSERİ / TURKEY














### *12. KAYSERİ OSB FEVZİ MERCAN MOSQUE / TURKEY*












### *12. KAYSERİ OSB FEVZİ MERCAN MOSQUE / TURKEY*














### 13. TURK FATIH TUTAK RESTAURANT / TURKEY



















### TWIN ARE DATASHEET








51

CREE IN THE MARK HIM CONSTRA


	r	
MODEL /SIZE	ARE	
INTERIOR/EXTERIOR	INTERIOR	
LED	CREE / SAMSUNG / SEOUL	
POWER	1W	
ССТ	2700K-3000K-4000K-6500K	
CRI	80+	
VOLTAGE	220V C.C. (EXTERNAL DRIVER)	
BEAM ANGLE	20°	
LUMEN OUTPUT	95LM	
STORAGE TEMPERATURE	-40C / +80C	
OPERATING TEMPERATURE	-40C / +60C	
CONTROL	ON-OFF / DALI	
DIMENSIONS (mm)	Q/H: 45/51	
PANEL CUT OUT (mm)	Q: 35	
HOUSING	DIA ALU	
CABLES	RUBBER	
WARRANTY	2 YEARS	
IP	IP20	






### TWIN BONA DATASHEET








MODEL /SIZE	BONA
INTERIOR/EXTERIOR	EXTERIOR
LED	CREE / SAMSUNG / SEOUL
POWER	3W
ССТ	2700K-3000K-4000K-6500K
CRI	80+
VOLTAGE	12-24VDC
BEAM ANGLE	60°
LUMEN OUTPUT	66LM
STORAGE TEMPERATURE	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V
DIMENSIONS (mm)	W/H/L: 120/120/32.5
HOUSING	DIA ALU
CABLES	RUBBER
WARRANTY	2 YEARS
IP	IP67


#### GAMMA ANGLES:






#### TWIN BORKA DATASHEET





MODEL /SIZE	BORKA	
INTERIOR/EXTERIOR	INTERIOR	
LED	CREE / SAMSUNG / SEOUL	
POWER	12W	
ССТ	2700K-3000K-4000K	
CRI	80+	
VOLTAGE	220V C.C.	
BEAM ANGLE	10° - 25° - 40°	
LUMEN OUTPUT	931LM	
STORAGE TEMPERATURE	-40C / +80C	
OPERATING TEMPERATURE	-40C / +60C	
CONTROL	ON-OFF / DALI	
DIMENSIONS (mm)	Q/H: 59/125	
HOUSING	DIA ALU, UV STABILIZED PMMA	
CABLES	RUBBER	
WARRANTY	2 YEARS	
IP	IP20	


#### GAMMA ANGLES:






#### TWIN CALDE DATASHEET





MODEL /SIZE	CALDE	CLYDE
INTERIOR/EXTERIOR	EXTERIOR	INTERIOR
LED	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL
POWER	10W	10W
ССТ	2700K-3000K-4000K	2700K-3000K-4000K
CRI	80+	80+
VOLTAGE	220VAC	220VAC
BEAM ANGLE	10°,25°,40°,	10°,25°,40°,
LUMEN OUTPUT	88LM	88LM
STORAGE TEMPERATURE	-40C / +80C	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V	ON-OFF / DALI / 1-10V
DIMENSIONS (mm)	Q/H: 62/181	Q/H: 62/181
HOUSING	EXT ALU	EXT ALU
CABLES	RUBBER	RUBBER
WARRANTY	2 YEARS	2 YEARS
IP	IP67	IP20
		1


#### GAMMA ANGLES:







#### TWIN CALDE-X DATASHEET





MODEL /SIZE	CALDE X	CALDE X
INTERIOR/EXTERIOR	EXTERIOR	INTERIOR
LED	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL
POWER	10W	10W
ССТ	2700K-3000K-4000K	2700K-3000K-4000K
CRI	80+	80+
VOLTAGE	220VAC	220VAC
BEAM ANGLE	10°x40°, 25°x40°	10°x40°, 25°x40°
LUMEN OUTPUT	88LM	88LM
STORAGE TEMPERATURE	-40C / +80C	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V	ON-OFF / DALI / 1-10V
DIMENSIONS (mm)	Q/H: 62/181	Q/H: 62/181
HOUSING	EXT ALU	EXT ALU
CABLES	RUBBER	RUBBER
WARRANTY	2 YEARS	2 YEARS
IP	IP67	IP20
		I









### TWIN DANLA DATASHEET





MODEL /SIZE	DANLA	
INTERIOR/EXTERIOR	INTERIOR	
LED	CREE / SAMSUNG / SEOUL	
POWER	2W	
ССТ	2700K-3000K-4000K-6500K	
CRI	80+	
VOLTAGE	12-24VDC	
BEAM ANGLE	30°	
LUMEN OUTPUT	195LM	
STORAGE TEMPERATURE	-40C / +80C	
OPERATING TEMPERATURE	-40C / +60C	
CONTROL	ON-OFF / DALI	
DIMENSIONS (mm)	Q/H/: 38/40	
PANEL CUT OUT (mm)	Q: 32	
HOUSING	DIA ALU	
CABLES	RUBBER	
WARRANTY	2 YEARS	
IP	IP54	




30°




### TWIN DOWN DATASHEET





MODEL /SIZE	DOWN 4"	DOWN 6"
INTERIOR/EXTERIOR	INTERIOR	INTERIOR
LED	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL
POWER	12W	24W
ССТ	2700K-3000K-4000K-6500K	2700K-3000K-4000K-6500K
CRI	80+	80+
VOLTAGE	180-240VAC	180-240VAC
BEAM ANGLE	120°	120°
LUMEN OUTPUT	1200LM	2400LM
STORAGE TEMPERATURE	-40C / +80C	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V	ON-OFF / DALI / 1-10V
DIMENSIONS (mm)	Q: 120	Q: 177
PANEL CUTOUT (mm)	Q: 105	Q: 152
HOUSING	ALUMINIUM, PMMA	ALUMINIUM, PMMA
CABLES	RUBBER	RUBBER
WARRANTY	5 YEARS	5 YEARS
IP	IP20	IP20









#### TWIN FERRA DATASHEET



17°








MODEL /SIZE	FERRA-20W	FERRA-30W
INTERIOR/EXTERIOR	EXTERIOR	EXTERIOR
LED	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL
POWER	20W	30W
ССТ	2700K-3000K-4000K-5000K	2700K-3000K-4000K-5000K
CRI	80+	80+
VOLTAGE	180-240VAC	180-240VAC
BEAM ANGLE	17° - 30° - 50°	17° - 30° - 50°
LUMEN OUTPUT	1840LM	2700LM
STORAGE TEMPERATURE	-40C / +80C	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V	ON-OFF / DALI / 1-10V
DIMENSIONS (mm)	Q/W/H/L: 107/110/225/167	Q/W/H/L: 107/110/225/167
HOUSING	DIA ALU, TEMPERED GLASS	DIA ALU, TEMPERED GLASS
CABLES	RUBBER	RUBBER
WARRANTY	2 YEARS	2 YEARS
IP	67	67


#### GAMMA ANGLES:





#### TWIN GANA DATASHEET






MODEL /SIZE	GANA LS33	GANA LS66
INTERIOR/EXTERIOR	INTERIOR / EXTERIOR	INTERIOR / EXTERIOR
LED	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL
POWER	12W	24W
ССТ	2700K-3000K-4000K-6500K	2700K-3000K-4000K-6500K
CRI	80+	80+
VOLTAGE	110-277VDC	110-277VDC
BEAM ANGLE	10X60°	10X60°
LUMEN OUTPUT	1080LM	2160LM
STORAGE TEMPERATURE	-40C / +80C	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C	-40C / +60C
CONTROL	ON-OFF	ON-OFF
DIMENSIONS (mm)	W/H/L: 50/86/330	W/H/L: 50/86/660
HOUSING	EXT ALU, UV STABILIZED PMMA	EXT ALU, UV STABILIZED PMMA
CABLES	RUBBER	RUBBER
WARRANTY	5 YEARS	5 YEARS
IP	IP67	IP67

#### GAMMA ANGLES:

#### 10X60°







Fixed

CUTOUT

#### TWIN HINA DATASHEET








MODEL /SIZE	HINA-11W	
INTERIOR/EXTERIOR	INTERIOR	
LED	CREE / SAMSUNG / SEOUL	
POWER	11W / 700mA	
ССТ	2700К-3000К-4000К	
CRI	80+	
VOLTAGE	180-240VAC	
BEAM ANGLE	10° - 25° - 40°	
LUMEN OUTPUT	880LM	
STORAGE TEMPERATURE	-40C / +80C	
OPERATING TEMPERATURE	-40C / +60C	
CONTROL	ON-OFF / DALI / 1-10V	
DIMENSIONS (mm)	Q/H: 80/75	
PANEL CUT OUT (mm)	Q: 72	
HOUSING	EXT ALU, PMMA	
CABLES	RUBBER	
WARRANTY	2 YEARS	
IP	IP20 / IP44	










### TWIN JINA DATASHEET










MODEL /SIZE	JINA-3W	JINA-6W
INTERIOR/EXTERIOR	EXTERIOR	EXTERIOR
LED	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL
POWER	3W	6W
ССТ	2700K-3000K-4000K-6500K	2700K-3000K-4000K-6500K
CRI	80+	80+
VOLTAGE	180-240VAC	180-240VAC
BEAM ANGLE	4° - 10° - 30°	4° - 10° - 30°
LUMEN OUTPUT	246LM	480LM
STORAGE TEMPERATURE	-40C / +80C	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V	ON-OFF / DALI / 1-10V
DIMENSIONS (mm)	Q/H: 49,5/138	Q/H: 49,5/138
HOUSING	EXT. ALU, TEMPERED GLASS, HONEYCOMB	EXT. ALU, TEMPERED GLASS, HONEYCOME LOUVRE
CABLES	RUBBER	RUBBER
WARRANTY	2 YEARS	2 YEARS
IP	67	67
DRIVER	OUTSIDE	OUTSIDE

#### GAMMA ANGLES:

10°









Π

Î

4°




### TWIN KAE DATASHEET





MODEL /SIZE	KAE-T	KAE-B
INTERIOR/EXTERIOR	EXTERIOR	EXTERIOR
LED	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL
POWER	10-15W	10-15W
ССТ	2700K-3000K-4000K	2700K-3000K-4000K
CRI	80+	80+
VOLTAGE	48VDC / 220VAC	48VDC / 220VAC
BEAM ANGLE	10° - 25° - 40°	10° - 25° - 40°
LUMEN OUTPUT	1100LM-1650LM	1100LM-1650LM
STORAGE TEMPERATURE	-40C / +80C	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V	ON-OFF / DALI / 1-10V
DIMENSIONS (mm)	Q/H: 90/330	Q/H: 90/170
HOUSING	DIA ALU, TEMPERED GLASS	DIA ALU, TEMPERED GLASS
CABLES	RUBBER	RUBBER
WARRANTY	2 YEARS	2 YEARS
IP	IP67	IP67

GAMMA ANGLES:






CREE® CE 62


### TWIN LAKU DATASHEET






MODEL /SIZE	LAKU-600	LAKU-1200
INTERIOR/EXTERIOR	INTERIOR / EXTERIOR	INTERIOR / EXTERIOR
LED	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL
POWER	20W	40W
ССТ	2700K-3000K-4000K-6500K	2700K-3000K-4000K-6500K
CRI	80+	80+
VOLTAGE	110-277VDC	110-277VDC
BEAM ANGLE	120°	120°
LUMEN OUTPUT	2240LM	4480LM
STORAGE TEMPERATURE	-40C / +80C	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V	ON-OFF / DALI / 1-10V
DIMENSIONS (mm)	W/H/L: 55/45/600	W/H/L: 55/45/1200
HOUSING	EXT ALU, UV STABILIZED PMMA	EXT ALU, UV STABILIZED PMMA
CABLES	RUBBER	RUBBER
WARRANTY	2 YEARS GAMMA ANGLES:	2 YEARS
IP	IP44	IP44


#### GAMMA ANGLES:







### TWIN MIKRO DATASHEET








MODEL /SIZE	Mikro
INTERIOR/EXTERIOR	INTERIOR / EXTERIOR
LED	CREE / SAMSUNG / SEOUL
POWER	3W
ССТ	2700K-3000K-4000K-6500K
CRI	80+
VOLTAGE	220V C.C. ( EXTERNAL DRIVER )
BEAM ANGLE	19°, 35°, 20X40°
LUMEN OUTPUT	276LM
STORAGE TEMPERATURE	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V
DIMENSIONS (mm)	Q/H: 32,5/90
HOUSING	EXT ALU, TEMPERED GLASS
CABLES	RUBBER
WARRANTY	2 YEARS
IP	IP67









#### TWIN RENA DATASHEET






MODEL /SIZE	RENA LS32	RENA LS62	RENA LS92	RENA LS122
INTERIOR/EXTERIOR	INTERIOR / EXTERIOR	INTERIOR / EXTERIOR	INTERIOR / EXTERIOR	INTERIOR / EXTERIOR
LED	CREE / SAMSUNG /	CREE / SAMSUNG /	CREE / SAMSUNG /	CREE / SAMSUNG /
	SEOUL	SEOUL	SEOUL	SEOUL
POWER	14W	27W	40W	53W
ССТ	2700K-3000K-4000K-	2700K-3000K-4000K-	2700K-3000K-4000K-	2700K-3000K-4000K-
	6500K	6500K	6500K	6500K
CRI	80+	80+	80+	80+
VOLTAGE	110-277VDC	110-277VDC	110-277VDC	110-277VDC
BEAM ANGLE	10°, 15°, 25°,	10°, 15°, 25°,	10°, 15°, 25°,	10°, 15°, 25°,
	10X60°, 20X45°	10X60°, 20X45°	10X60°, 20X45°	10X60°, 20X45°
LUMEN OUTPUT	1200LM	2700LM	4000LM	5300LM
STORAGE TEMPERATURE	-40C / +80C	-40C / +80C	-40C / +80C	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C	-40C / +60C	-40C / +60C	-40C / +60C
CONTROL	ON-OFF / DALI / PWM /	ON-OFF / DALI / PWM /	ON-OFF / DALI / PWM /	ON-OFF / DALI / PWM /
	DMX	DMX	DMX	DMX
DIMENSIONS (mm)	W/H/L: 48/75/320	W/H/L: 48/75/620	W/H/L: 48/75/920	W/H/L: 48/75/1220
HOUSING	EXT ALU, UV STABILIZED	EXT ALU, UV STABILIZED	EXT ALU, UV STABILIZED	EXT ALU, UV STABILIZED
	PMMA	PMMA	PMMA	PMMA
CABLES	RUBBER	RUBBER	RUBBER	RUBBER
WARRANTY	5 YEARS	5 YEARS	5 YEARS	5 YEARS
IP	IP67	IP67	IP67	IP67













#### 10X60°




₩₩₩ WHENEXED NO. 65 CREE III Kipt for you

### TWIN SERA DATASHEET







MODEL /SIZE	SERA
INTERIOR/EXTERIOR	INTERIOR / EXTERIOR
LED	CREE / SAMSUNG / SEOUL
POWER	24W/MT
ССТ	2700K-3000K-4000K-6500K
CRI	80+
VOLTAGE	24VDC
BEAM ANGLE	52°
LUMEN OUTPUT	2200LM/MT
STORAGE TEMPERATURE	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C
CONTROL	ON-OFF / DALI
DIMENSIONS (mm)	W/H: 37/60
HOUSING	EXT ALU, UV STABILIZED PMMA
CABLES	RUBBER
WARRANTY	2 YEARS
IP	IP54, IP65
t	






### TWIN SERA LOTUS DATASHEET





MODEL /SIZE	SERA LOTUS
INTERIOR/EXTERIOR	INTERIOR / EXTERIOR
LED	CREE / SAMSUNG / SEOUL
POWER	36W
ССТ	2500K-2700K-3000K-4000K-6500K-R-G-B
CRI	80+
VOLTAGE	24 VDC / 220V C.V. (EXTERNAL DRIVER)
BEAM ANGLE	120°
LUMEN OUTPUT	570LM/MT, 2850LM/MT
STORAGE TEMPERATURE	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C
CONTROL	ON-OFF / DALI
DIMENSIONS (mm)	W/H: 48/77
HOUSING	EXT ALU, UV STABILIZED PMMA
CABLES	RUBBER
WARRANTY	2 YEARS
IP	IP54, IP65, IP68









#### TWIN SERO DATASHEET






MODEL /SIZE	SERO
INTERIOR/EXTERIOR	INTERIOR/EXTERIOR
LED	CREE / SAMSUNG / SEOUL
POWER	2W
ССТ	2700K-3000K-4000K-6500K
CRI	80+
VOLTAGE	12-24VDC
BEAM ANGLE	85°
LUMEN OUTPUT	295LM
STORAGE TEMPERATURE	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V
DIMENSIONS (mm)	Q/H: 99/54
PANEL CUT OUT (mm)	Q:91
HOUSING	DIA ALU, TEMPERED GLASS, PMMA
CABLES	RUBBER
WARRANTY	2 YEARS
IP	IP67






### TWIN SERRA DATASHEET







INTERIOR/EXTERIORINTERIORLEDCREE / SAMSUNG / SEOULPOWER40WCCT2700K-3000K-4000K-6500KCRI80+VOLTAGE110-277VDCBEAM ANGLE15°, 24°, 36°, 40°LUMEN OUTPUT5200LMSTORAGE TEMPERATURE-10C / +50COPERATING TEMPERATURE0N-OFF / DALIDIMENSIONS (mm)Q/H: 101/205HOUSINGRUBBERKARRANTY2 YEARS	MODEL /SIZE	SERRA
POWER40WCCT2700K-3000K-4000K-6500KCRI80+VOLTAGE110-277VDCBEAM ANGLE15°, 24°, 36°, 40°LUMEN OUTPUT5200LMSTORAGE TEMPERATURE-10C / +50COPERATING TEMPERATURE-40C / +60CCONTROLON-OFF / DALIDIMENSIONS (mm)Q/H: 101/205HOUSINGALUMINIUM, TEMPERED GLASSCABLESRUBBER	INTERIOR/EXTERIOR	INTERIOR
CCT         2700K-3000K-4000K-6500K           CRI         80+           VOLTAGE         110-277VDC           BEAM ANGLE         15°, 24°, 36°, 40°           LUMEN OUTPUT         5200LM           STORAGE TEMPERATURE         -10C / +50C           OPERATING TEMPERATURE         -40C / +60C           DIMENSIONS (mm)         Q/H: 101/205           HOUSING         ALUMINIUM, TEMPERED GLASS           CABLES         RUBBER	LED	CREE / SAMSUNG / SEOUL
CRI80+VOLTAGE110-277VDCBEAM ANGLE15°, 24°, 36°, 40°LUMEN OUTPUT5200LMSTORAGE TEMPERATURE-10C / +50COPERATING TEMPERATURE-40C / +60CCONTROLON-OFF / DALIDIMENSIONS (mm)Q/H: 101/205HOUSINGALUMINIUM, TEMPERED GLASSCABLESRUBBER	POWER	40W
VOLTAGE110-277VDCBEAM ANGLE15°, 24°, 36°, 40°LUMEN OUTPUT5200LMSTORAGE TEMPERATURE-10C / +50COPERATING TEMPERATURE-40C / +60CCONTROLON-OFF / DALIDIMENSIONS (mm)Q/H: 101/205HOUSINGALUMINIUM, TEMPERED GLASSCABLESRUBBER	ССТ	2700K-3000K-4000K-6500K
BEAM ANGLE15°, 24°, 36°, 40°LUMEN OUTPUT5200LMSTORAGE TEMPERATURE-10C / +50COPERATING TEMPERATURE-40C / +60CCONTROLON-OFF / DALIDIMENSIONS (mm)Q/H: 101/205HOUSINGALUMINIUM, TEMPERED GLASSCABLESRUBBER	CRI	80+
LUMEN OUTPUT5200LMSTORAGE TEMPERATURE-10C / +50COPERATING TEMPERATURE-40C / +60CCONTROLON-OFF / DALIDIMENSIONS (mm)Q/H: 101/205HOUSINGALUMINIUM, TEMPERED GLASSCABLESRUBBER	VOLTAGE	110-277VDC
STORAGE TEMPERATURE-10C / +50COPERATING TEMPERATURE-40C / +60CCONTROLON-OFF / DALIDIMENSIONS (mm)Q/H: 101/205HOUSINGALUMINIUM, TEMPERED GLASSCABLESRUBBER	BEAM ANGLE	15°, 24°, 36°, 40°
OPERATING TEMPERATURE     -40C / +60C       CONTROL     ON-OFF / DALI       DIMENSIONS (mm)     Q/H: 101/205       HOUSING     ALUMINIUM, TEMPERED GLASS       CABLES     RUBBER	LUMEN OUTPUT	5200LM
CONTROL     ON-OFF / DALI       DIMENSIONS (mm)     Q/H: 101/205       HOUSING     ALUMINIUM, TEMPERED GLASS       CABLES     RUBBER	STORAGE TEMPERATURE	-10C / +50C
DIMENSIONS (mm)     Q/H: 101/205       HOUSING     ALUMINIUM, TEMPERED GLASS       CABLES     RUBBER	OPERATING TEMPERATURE	-40C / +60C
HOUSING     ALUMINIUM, TEMPERED GLASS       CABLES     RUBBER	CONTROL	ON-OFF / DALI
CABLES RUBBER	DIMENSIONS (mm)	Q/H: 101/205
	HOUSING	ALUMINIUM, TEMPERED GLASS
WARRANTY 2 YEARS	CABLES	RUBBER
	WARRANTY	2 YEARS
IP IP20	IP	IP20


#### GAMMA ANGLES:











CREE CREE CE 69

#### TWIN STRIPLINE DATASHEET


......

1. ....

.....

MODEL /SIZE	STRIP 56LED/MT
INTERIOR/EXTERIOR	EXTERIOR
LED	CREE / SAMSUNG / SEOUL
POWER	8W - 10W - 14W
ССТ	2700К -3000К – 4000К – 6500К
CRI	80+
VOLTAGE	24VDC
BEAM ANGLE	177°
LUMEN OUTPUT	131LM
STORAGE TEMPERATURE	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C
CONTROL	ON-OFF / DALI
DIMENSIONS (mm)	W/H/L: 16/2,2/1000
HOUSING	EXT ALU, PMMA
CABLES	PVC / RUBBER
WARRANTY	2 YEARS
IP	IP65

#### GAMMA ANGLES:







## COMPANY PROFILE 2022

#### TWIN TALIA DATASHEET








MODEL /SIZE	TALIA		
INTERIOR/EXTERIOR	EXTERIOR		
LED	CREE / SAMSUNG / SEOUL		
POWER	7W		
ССТ	2700K-3000K-4000K-5000K		
CRI	80+		
VOLTAGE	12-24VDC		
BEAM ANGLE	135°		
LUMEN OUTPUT	180LM		
STORAGE TEMPERATURE	-40C / +80C		
OPERATING TEMPERATURE	-40C / +60C		
CONTROL	ON-OFF / DALI / 1-10V		
DIMENSIONS (mm)	Q/H: 110/74		
PANEL CUT OUT (mm)	Q: 98		
HOUSING	DIA ALU, PMMA		
CABLES	RUBBER		
WARRANTY	2 YEARS		
IP	IP67		

#### GAMMA ANGLES:








# COMPANY PROFILE 2022


#### TWIN YEMEN DATASHEET






MODEL /SIZE	YEMEN LS32	YEMEN LS62	YEMEN LS92	YEMEN LS122
INTERIOR/EXTERIOR	INTERIOR	INTERIOR	INTERIOR	INTERIOR
LED	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL	CREE / SAMSUNG / SEOUL
POWER	14W	27W	40W	53W
ССТ	2700K-3000K-4000K- 6500K	2700K-3000K-4000K- 6500K	2700K-3000K-4000K- 6500K	2700K-3000K-4000K- 6500K
CRI	80+	80+	80+	80+
VOLTAGE	110-277VDC	110-277VDC	110-277VDC	110-277VDC
BEAM ANGLE	15°, 25°, 40°, 20x45°	15°, 25°, 40°, 20x45°	15°, 25°, 40°, 20x45°	15°, 25°, 40°, 20x45°
LUMEN OUTPUT	1400LM	2700LM	4000LM	5300LM
STORAGE TEMPERATURE	-40C / +80C	-40C / +80C	-40C / +80C	-40C / +80C
OPERATING TEMPERATURE	-40C / +60C	-40C / +60C	-40C / +60C	-40C / +60C
CONTROL	ON-OFF / DALI / 1-10V	ON-OFF / DALI / 1-10V	ON-OFF / DALI / 1-10V	ON-OFF / DALI / 1-10\
DIMENSIONS (mm)	W/H/L: 31,5/58/310	W/H/L: 31,5/58/610	W/H/L: 31,5/58/910	W/H/L: 31,5/58/1210
HOUSING	EXT ALU, UV STABILIZED PMMA	EXT ALU, UV STABILIZED PMMA	EXT ALU, UV STABILIZED PMMA	EXT ALU, UV STABILIZ PMMA
CABLES	RUBBER	RUBBER	RUBBER	RUBBER
WARRANTY	5 YEARS	5 YEARS	5 YEARS	5 YEARS
IP	IP40	IP40	IP40	IP40








#### GAMMA ANGLES:

40°




#### 20X45°








#### **SAMPLE 00001**




DESCRIPTION: Bespoke pendant lighting fixture with frosted glass diffuser type including 3xE27 lamp holder with LED light source 6W 2700K. 220–240V dimmable by phase.



**DESCRIPTION:** Decorative Pendant Light, Dimmable by Phase, IP20






**DESCRIPTION:** Bespoke pendant lighting fixture with frosted glass diffuser type including 3xE27 lamp holder with LED light source 6W 2700K. 220–240V dimmable by phase.

#### **SAMPLE 00004**









**DESCRIPTION:** Bespoke pendant lighting fixture with frosted glass diffuser type including 3xE27 lamp holder with LED light source 6W 2700K. 220–240V dimmable by phase.







#### **SAMPLE 00006**



DESCRIPTION: Floor Ceiling Lamp with Fringes type flbatjour, Dimmable by Phase




































































































## Referances



